

5.0MP 30x H.265 HD IP PTZ Dome Camera

5MP
SUPER HD

30X+
OPTICAL

H.265
High Efficiency Video Coding



Description:
VSENSE
AVC-69IP5030PZ

Key Features:

- 1/2.7" 5.0Megapixel CMOS sensor
- H.265/H.264, Dual Stream, Max 2592x 1944 Resolution
- 30x Optical motorized zoom lens
- Day/Night, AWB/MWB,BLC, HLC, 2D/3D-DNR,Shutter, IR-CUT, D-WDR, Mirror, rotate, Defogging
- Multiply Style OSD Overlay, Motion Detection, Privacy Mask, RTSP and Onvif 17.06 compatible with many third-party NVR
- Easy-to-use P2P Cloud service, Support user authentication, video data encryption, Support Alarm Snapshot to Email and FTP
- Multiply WEB browser IE, Firefox 32bit ESR, PC Client, Mobile APP remote access
- Pan/Tilt/Zoom, 360 rotate, 90 auto flip, Horizontal Rotation Speed 0.5°~40°/s, Vertical rotation speed 0.5°~40°/s
- Support 128 presets, 8 cruise, Scanning, Parking support preset, Scan/Cruise
- Lightning protection 4000V
- 8 pcs Array IR Led, IR distance 100 meters
- DC12V, POE, IP66



Specification:

Model	AVC-69IP5030PZ
Camera	
Image Sensor	1/2.7" 5.0 Megapixels CMOS
Effective Pixels	2592x1944@20fps
Electronic Shutter	AUTO, 1/25s ~ 1/100000s
Min. Illumination	0.01Lux@F1.2(AGC ON), 0Lux IR on
Day/Night	Auto/Color/(B/W)/Timing
WDR	Digital WDR
White Balance	Auto/Manual
AGC/BLC/HLC	Support
DNR	2D/3D DNR
Other	Multi-lines OSD, Motion Detection, Privacy Mask, Mirror
Encode	
Video Standard	H.265/H.264
Video Resolution	Main Stream: 20fps@5MP(2592x1944),30fps@4MP/3MP,30fps@1080P/720P
	Sub Stream: D1/VGA(640x480)/360P/QVGA@25fps
Video Bitrates	32Kbps - 8Mbps, VBR/CBR
Audio Standard	G.711-u/G.711-a
OSD Overlay	Title and Time overlay
IR Led	
IR Led	8pcs array IR Led (4 near + 4 far)
IR Distance	100 M
Lens	
Focal length	5~150mm
IRIS	F1.5-22
View angle	68 - 2.8°
Zoom	30x optical zoom

Other Function (Optional)	
Standard	IEEE 802.3af/at , high power
Audio	Internal Microphone
PTZ	
Pan/Tilt Range	Pan: 0° ~ 360°; Tilt: 0° ~ 90°
Preset Point	225
Control Speed	Pan: 0.5° ~240° /s; Tilt: 0.5° ~180° /s
A-B Scanning	Support
Auto Cruising	Support 8 groups
Power on Action	Preset/Scan/Cruise
Power-off Recovery	Support
Network Services	
Protocol	HTTP/RTSP/FTP/NFS/SMTP/DHCP/NTP, etc.
P2P	Yes
Web	IE , Firefox (32bit esr), etc.
Media	CMS, Android, IOS
ONVIF	17.06 compatible
General	
Network Port	1-RJ45, 100Mbps, PoE 48V in
Power Supply	12 VDC ± 10% 2A
Power Consumption	< 20 W
Operating Temp.	-30°C-(+60)°C, 10%-90%RH
Size	Φ137(mm)×234(mm)
Weight	2.2kg